

TECHNICAL SPECIFICATION APRIL 2022



POWERTRAIN	D165 MHEV	D200 MHEV	D300 MHEV
Transmission	Automatic	Automatic	Automatic
Driveline	AWD	AWD	AWD
Maximum power (PS / kW / rpm)	163 / 120 / 3.750	204 / 150 / 3.750	300 / 221 / 4.000
Maximum torque (Nm / rpm)	380 / 1.500-2.500	430 / 1.750-2.500	650 / 1.500-2.500
Capacity (cc)	1.997	1.997	2.996
No. of cylinders / Valves per cylinder	4 / 4	4 / 4	6 / 4
Cylinder layout	Inline	Inline	Inline
Bore / stroke (mm)	83 / 92,31	83 / 92,31	83 / 92,31
Compression ratio (:1)	16,5+ / -0,5	16,5+ / -0,5	15,5
PERFORMANCE			
Acceleration (secs) 0-100 km/h (0-60 mph)	9,9 (9,2)	8,0 (7,6)	6,4 (6,1)
Maximum speed km/h (mph)	195 (121)	210 (130)	230 (143)
BRAKES			
Front type		Single Piston Sliding Caliper, Vented Disc	
Front diameter (mm)	350	350	370
Rear type		Single Piston Sliding Caliper, Vented Disc	
Rear diameter (mm)	325	325	325
Park Brake		iEPB, motor on caliper	

Some features on images may vary between optional and standard for different model years and due to the impact of Covid-19, many of our images have not been updated to reflect 23MY specifications. Please refer to the car configurator and additionally consult your local Retailer for detailed 23MY specifications and do not base an order on website imagery alone. Jaguar Land Rover Limited is constantly seeking ways to improve the specification, design and production of its vehicles, parts and accessories and alterations take place continually, and we reserve the right to change without notice.

WEIGHTS (kg)*	D165 MHEV	D200 MHEV	D300 MHEV
Unladen weight (EU)**	1.951	1.951	2.083
Unladen weight (DIN) ⁺	1.876	1.876	2.008
Gross Vehicle Weight (GVW)	2.540	2.540	2.660
TOWING (kg)			
Unbraked trailer	750	750	750
Maximum towing	2.400	2.400	2.400
Maximum coupling point (nose weight)	100	100	100
Maximum vehicle and trailer combination	4.940	4.940	5.060
ROOF CARRYING (kg)			
Maximum roof load (including cross bars)	75	75	75

FUEL ECONOMY Fuel tank capacity – useable litres		D165 MHEV 62		D200 MHEV 62		D300	MHEV	
						68		
Diesel/Gasoline Particul	Diesel/Gasoline Particulate Filter (DPF/GPF)							
NEDC EQUIVALENT (NI			Class A	Class B	Class A	Class B	Class A	Class B
	Urban	l/100km (mpg)	5,7 (49,6)	5,8 (48,7)	5,7 (49,6)	5,8 (48,7)	9,0 (31,4)	9,0 (31,4)
NEDC2 Consumption	Extra Urban	l/100km (mpg)	4,9 (57,6)	4,9 (57,6)	4,9 (57,6)	4,9 (57,6)	5,8 (48,8)	5,8 (48,8)
	Combined	l/100km (mpg)	5,2 (54,3)	5,2 (54,3)	5,2 (54,3)	5,2 (54,3)	6,9 (40,7)	6,9 (40,7)
	Urban	(g/km)	151	153	151	153	237	237
NEDC2 CO ₂ Emissions	Extra Urban	(g/km)	128	129	128	129	153	153
2	Combined	(g/km)	137	138	137	138	183	183
WLTP**								
	Low	l/100km (mpg)	7,5-7,7 (3	37,7-36,7)	7,5-7,8 (3	37,7-36,2)	10,5-10,9 (26,9-25,9) 7,7-7,8 (36,7-36,2)	
	Medium	l/100km (mpg)	6,1-6,5 (4	16,3-43,5)	6,1-6,6 (4	6,3-42,8)		
WLTP Consumption	High	l/100km (mpg)	5,3-5,8 (5	53,3-48,7)	5,3-5,9 (53,3-47,9) 6,6-7,2 (42,8-39,2)	6,0-6,4 (47,1-44,1) 7,4-7,9 (38,2-35,8)		
	Extra High	l/100km (mpg)	6,6-7,1 (4	2,8-39,8)				
	Combined	l/100km (mpg)	6,2-6,6 (4	45,6-42,8)	6,2-6,7 (45,6-42,2)		7,4-7,8 (38,2-36,2)	
	Low	(g/km)	197·	-203	197-	204	274	-285
	Medium	(g/km)	159	9-171	159-172		201-	-204
WLTP CO ₂ Emissions	High	(g/km)	140-151		140	-154	157	-168
_	Extra High	(g/km)	173	-185	173	-189	193-	-206
	Combined	(g/km)	163	-174	163	-177	194-	-205

Standard.

Class A (18" and 19" wheels) Class B (20"-22" wheels).

*The figures provided are NEDC2 calculated from official manufacturer's WLTP tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO₂ and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted. NEDC2 are figures calculated using a Government formula from WLTP figures equivalent to what they would have been under the old NEDC test. The correct tax treatment can then be applied. **The figures provided are as a result of official manufacturer's tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO₂ and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted.

POWERTRAIN	D200	D300
Transmission	Automatic	Automatic
Driveline	AWD	AWD
Maximum power (PS / kW / rpm)	199 / 146 / 3.750	300 / 221 / 4.000
Maximum torque (Nm / rpm)	430 / 1.750-2.500	650 / 1.500-2.500
Capacity (cc)	1.997	2.996
No. of cylinders / Valves per cylinder	4 / 4	6 / 4
Cylinder layout	Inline	Inline
Bore / stroke (mm)	83 / 92,31	83 / 92,31
Compression ratio (:1)	16,5+ / -0,5	15,5
PERFORMANCE		
Acceleration (secs) 0-100 km/h (0-60 mph)	8,0 (7,6)	6,4 (6,1)
Maximum speed km/h (mph)	210 (130)	230 (143)
BRAKES		
Front type	Single Piston Sliding	Caliper, Vented Disc
Front diameter (mm)	350	370
Rear type	Single Piston Sliding	Caliper, Vented Disc
Rear diameter (mm)	325	325
Park Brake	iEPB, moto	or on caliper

WEIGHTS (kg)*	D200	D300
Unladen weight (EU)**	1.900	2.017
Unladen weight (DIN) ⁺	1.825	1.942
Gross Vehicle Weight (GVW)	2.540	2.660
TOWING (kg)		
Unbraked trailer	750	750
Maximum towing	2.400	2.400
Maximum coupling point (nose weight)	100	100
Maximum vehicle and trailer combination	4.940	5.060
ROOF CARRYING (kg)		
Maximum roof load (including cross bars)	75	75

FUEL ECONOMY			D200	D300
Fuel tank capacity -	useable litres		62	68
Diesel/Gasoline Par	ticulate Filter (DPF/G	PF)		
NEDC*				
Consumption	Combined	l/100km	5,9	7,3
CO ₂ Emissions	Combined	(g/km)	156	193

POWERTRAIN	P250	P340 MHEV	P400 MHEV
Transmission	Automatic	Automatic	Automatic
Driveline	AWD	AWD	AWD
Maximum power (PS / kW / rpm)	250 / 184 / 5.500	340 / 250 / 5.500-6.500	400 / 294 / 5.500-6.500
Maximum torque (Nm / rpm)	365 / 1.300-4.500	480 / 1.500-4.500	550 / 2.000-5.000
Capacity (cc)	1.997	2.995	2.995
No. of cylinders / Valves per cylinder	4 / 4	6 / 4	6 / 4
Cylinder layout	Inline	Inline	Inline
Bore / stroke (mm)	83 / 92,29	83 / 92,29	83 / 92,29
Compression ratio (:1)	10,5+ / -0,5	10,5	10,5
PERFORMANCE			
Acceleration (secs) 0-100 km/h (0-60 mph)	7,3 (6,9)	6,1 (5,8)	5,4 (5,1)
Maximum speed km/h (mph)	217 (135)	240 (149)	250 (155)
ELECTRIC MOTOR DATA			
Maximum Power PS (kW)	_	-	_
Maximum Torque (Nm)	_	_	-
BRAKES			
Front type		Single Piston Sliding Caliper, Vented Disc	
Front diameter (mm)	350	370	370
Rear type		Single Piston Sliding Caliper, Vented Disc	
Rear diameter (mm)	325	325	325
Park Brake		iEPB, motor on caliper	

POWERTRAIN	P400e PHEV	P550 SVR
Transmission	Automatic	Automatic
Driveline	AWD	AWD
Maximum power (PS / kW / rpm)	404 / 297 / 5.500*	550 / 405 / 6.250-6.500
Maximum torque (Nm / rpm)	640 / 1.500-4.400*	700 / 3.500-5.000
Capacity (cc)	1.997	5.000
No. of cylinders / Valves per cylinder	4 / 4	8 / 4
Cylinder layout	Inline	Longitudinal V
Bore / stroke (mm)	83 / 92,29	92,5 / 93
Compression ratio (:1)	9,5+ / -0,5	9,5
PERFORMANCE		
Acceleration (secs) 0-100 km/h (0-60 mph)	5,3 (5,0)	4,0 (3,8)
Maximum speed km/h (mph)	240 (149)	286 (178)
ELECTRIC MOTOR DATA		
Maximum Power PS (kW)	143 (105)	_
Maximum Torque (Nm)	275	_
BRAKES		
Front type	Single Piston Sliding Caliper, Vented Disc	4-Piston Aluminium Monobloc Fixed Caliper, Vented 2-Piece Disc
Front diameter (mm)	370	395
Rear type	Single Piston Sliding Caliper, Vented Disc	Single Piston Sliding Caliper, Vented Disc
Rear diameter (mm)	325	396
Park Brake	iEPB, motor on caliper	iEPB, motor on caliper

- Not available.

*When combined with electric motor.

WEIGHTS (kg)*	P250	P340 MHEV	P400 MHEV
Unladen weight (EU)**	1.897	TBC	2.028
Unladen weight (DIN) ⁺	1.822	TBC	1.953
Gross Vehicle Weight (GVW)	2.520	TBC	2.600
TOWING (kg)			
Unbraked trailer	750	TBC	750
Maximum towing	2.400	TBC	2.400
Maximum coupling point (nose weight)	100	TBC	100
Maximum vehicle and trailer combination	4.920	TBC	5.000
ROOF CARRYING (kg)			
Maximum roof load (including cross bars)	75	75	75

BATTERY AND CHARGING TIMES	P400e PHEV
Home Charger/Wall box 7kW	2 hours 16 mins to 100%
DC Charger 50kW	30 mins to 80% / 1 hour 13 mins to 100%
Domestic Plug 2,3kW	7 hours 6 mins to 100%
Battery capacity (Usable) kWh	13,6
Charging cable length (m)	5
WEIGHTS (kg)*	
Unladen weight (EU)**	2.189
Unladen weight (DIN)†	2.114
Gross Vehicle Weight (GVW)	2.690
TOWING (kg)	
Unbraked trailer	750
Maximum towing	2.000
Maximum coupling point (nose weight)	100
Maximum vehicle and trailer combination	4.690
ROOF CARRYING (kg)	
Maximum roof load (including cross bars)	75

P550 SVR

_	
_	
_	
_	
_	
2.133	
2.058	
2.590	
750	
2.400	
100	
4.990	

75

FUEL ECONOMY Fuel tank capacity - useable litres		P250 83		P340	MHEV	P400	MHEV		
				83		83			
Diesel/Gasoline Particul	esel/Gasoline Particulate Filter (DPF/GPF)								
EV Range Class A Comb	bined (NEDC2)*	km/miles		-		-		-	
EV Range TEL Combine	ed (WLTP)**	km/miles		-		-		_	
NEDC EQUIVALENT (N	EDC2)*		Class A	Class B	Class A	Class B	Class A	Class B	
	Urban	l/100km (mpg)	9,4 (30,1)	9,6 (29,4)	TBC	TBC	11,9 (23,8)	11,9 (23,8)	
NEDC2 Consumption	Extra Urban	l/100km (mpg)	6,7 (42,2)	6,8 (41,5)	TBC	TBC	7,2 (39,2)	7,2 (39,2)	
	Combined	l/100km (mpg)	7,7 (36,7)	7,8 (36,2)	TBC	TBC	8,9 (31,7)	8,9 (31,7)	
NEDC2 CO ₂ Emissions	Urban	(g/km)	214	218	TBC	TBC	270	270	
	Extra Urban	(g/km)	151	154	TBC	TBC	164	164	
	Combined	(g/km)	174	177	TBC	TBC	202	202	
WLTP**									
	Low	l/100km (mpg)	12,6-13,1 (22,4-21,6)		_	14,4-14,8 (19,6-19,1)		
	Medium	l/100km (mpg)	9,1-9,9 (3	31,0-28,5)	-		9,6-10,2 (29,4-27,7)		
WLTP Consumption	High	l/100km (mpg)	7,9-8,7 (3	35,8-32,5)	-		8,3-8,7 (34,0-32,5) 9,5-10,1 (29,7-28,0)		
	Extra High	l/100km (mpg)	9,2-10,4 (30,7-27,2)					
	Combined	l/100km (mpg)	9,2-10,1 (3	30,7-28,0)		_	9,8-10,3 (28,8-27,4)	
	Low	(g/km)	283	-295	_		326-334		
	Medium	(g/km)	206-223		_		216-230		
WLTP CO ₂ Emissions	High	(g/km)	178	-197	-		188	-197	
	Extra High	(g/km)	208	-233		_	213	-227	
	Combined	(g/km)	208	-228		-	221	-233	

■ Standard – Not available.

Class A (18" and 19" wheels) Class B (20"-22" wheels).

*The figures provided are NEDC2 calculated from official manufacturer's WLTP tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO₂ and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted. NEDC2 are figures calculated using a Government formula from WLTP figures equivalent to what they would have been under the old NEDC test. The correct tax treatment can then be applied. **The figures provided are as a result of official manufacturer's tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO₂ and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted.

FUEL ECONOMY Fuel tank capacity – useable litres Diesel/Gasoline Particulate Filter (DPF/GPF)			P400e PHEV 69 ■		P550 SVR	
					83	
EV Range Class A Combined (NEDC2)* km/miles		59 / 37		-		
EV Range TEL Combined (WLTP)** km/miles		km/miles	53 / 33		_	
NEDC EQUIVALENT (NEDC2)*		Class A	Class B	Class B		
	Urban	l/100km (mpg)	_	_	15,8 (17,9)	
NEDC2 Consumption NEDC2 CO ₂ Emissions	Extra Urban	l/100km (mpg)	_	_	8,9 (31,7)	
	Combined	l/100km (mpg)	2,4 (117,7)	2,4 (117,7)	11,4 (24,8)	
	Urban	(g/km)	_	_	360	
	Extra Urban	(g/km)	_	_	202	
	Combined	(g/km)	54	54	260	
WLTP**						
WLTP Consumption	Low	l/100km (mpg)	_		18,9 (14,9)	
	Medium	l/100km (mpg)	_		12,1 (23,3)	
	High	l/100km (mpg)	_		10,3 (27,4)	
	Extra High	l/100km (mpg)	_		11,4 (24,8)	
	Combined	l/100km (mpg)	2,2-2,4 (128,4-117,7)		83 - - Class B 15,8 (17,9) 8,9 (31,7) 11,4 (24,8) 360 202 260 18,9 (14,9) 12,1 (23,3) 10,3 (27,4)	
WLTP CO ₂ Emissions	Low	(g/km)	_		426	
	Medium	(g/km)	_		273	
	High	(g/km)	_		233	
	Extra High	(g/km)	_		256	
	Combined	(g/km)	49-55		275	

■ Standard – Not available.

Class A (18" and 19" wheels) Class B (20"-22" wheels).

*The figures provided are NEDC2 calculated from official manufacturer's WLTP tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted. NEDC2 are figures calculated using a Government formula from WLTP figures equivalent to what they would have been under the old NEDC test. The correct tax treatment can then be applied. **The figures provided are as a result of official manufacturer's tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route.

F-PACE - DIMENSIONS

Vehicle Height - 1.664mm (1.670mm on SVR)

Headroom

Maximum front/rear headroom with Panoramic roof fitted 960 / 952mm Maximum front/rear headroom with standard roof 1.007 / 977mm

Legroom

Maximum front legroom 1.023mm Maximum rear legroom 944mm

Loadspace Capacity

Height 751mm, Width 1.091mm Loadspace width between arches 1.048mm Maximum loadspace volume behind first row Dry* Up to 1.440 litres, Wet** Up to 1.842 litres Maximum loadspace volume behind second row Dry* Up to 613 litres, Wet** Up to 793 litres

Turning Circle

Kerb-to-kerb 11,95m (12,01m on SVR) Wall-to-wall 12,39m (12,29m on SVR) Turns lock-to-lock 2,52



1.640,2mm (1.648,3mm on SVR)



1.655,7mm (1.665,9mm on SVR)



*Dry: Volume as measured with VDA-compliant solid blocks (200mm x 50mm x 100mm). **Wet: Volume as measured by simulating the loadspace filled with liquid. Volume measured up to the headliner. Boot configuration and total loadspace will vary by vehicle specification (model and powertrain) and market, and if full size spare or space saver spare wheel is fitted.

Dimensions were measured with vehicle at unladen weight.